

PNEUMATRON

www.pneumatron.co.za

sales01@pneumatron.co.za



2/2 Industrial Solenoid Valve P5W23 Series, Diaphragm Direct Lifting (N.O)

- Characteristics:**
1. Direct lifting diaphragm construction.
 2. Open from zero bar for low pressure system use.
 3. High frequency of DIN plug coil.

Medium: Air, Gas, Water, Light Oil (≤ 20 Centistokes)
Temperature: NBR: -10°C to 80°C
Pressure: P5W23 - 0 to 6 Bar(VAC)
Body: Nylon (PA66)
Port Size: 1 1/2" & 2"
Orifice (mm): DN 15, 20, 25, 32, 40, 50
Coil voltages: 12VDC/24VDC/220VAC
Coils: C41 (26VA (AC), 18W(DC)) - 11/2" to 2"

Material:

Body: Nylon (PA66)
 Seal: NBR (Buna)
 Armature Tube: Stainless Steel 304
 Plunger: Stainless Steel 430F
 Springs: SS304
 Shading Rings: Copper



P5W23 Series, Normally Open, With coil C41

Port Size	Orifice	Cv	Min Pressure	Max Pressure		Seals Material	Body Material	Valve Body	Coil
				AC(26VA)	DC(18W)				
1 1/2"	40	30.0	0 Bar	6 Bar	6 Bar	NBR (Buna)	Nylon (PA66)	P5W23NH40S14B	C41
2"	50	48.0	0 Bar	6 Bar	6 Bar			P5W23NH50S20B	C41

BODY DIMENSION CODE(Size in mm)				Valve Body
A	B	H	Port size	
140	112	170	1 1/2" (40)	P5W23NH40S14B
159	130	190	2" (50)	P5W23NH50S20B

