

PNEUMATRON


www.pneumatron.co.za

sales01@pneumatron.co.za

2/2 Industrial Solenoid Valve PD5422 Series, High Pressure Pilot Operated N.C

Characteristics:

1. High pressure solenoid valve pilot operated
2. With PTFE seals to improve the quality.



Medium: AIR, Water, Steam, Oil.
Temperature: PTFE: -10°C to 180°C
Pressure: PD5422: 1 to 50 Bar
Body: Brass
Port Size: 1/2"
Orifice (mm): DN 13
Coil voltages: 24VDC/220VAC
Coils: C20DX, 24VA (AC), 15W (DC), IP65, 100%ED-PD5422 series



Material:
 Body: Brass
 Seal: PTFE
 Armature Tube: Stainless Steel 304
 Plunger: Stainless Steel 430F
 Springs: SS 304
 Shading Rings: Stainless Steel 304

PD5422 Series - Normally Closed, with C20DX coil

Port Size	Orifice	Min Pressure	Max Pressure		Seals Material	Body Material	Valve No:	Coil
			AC(24VA)	DC(15W)				
1/2"	13	1 Bar	50 Bar	50 Bar	PTFE	Brass	PD5422BH15S04V	C20DX

Valve dimensions

BODY DIMENSION CODE(Size in mm)							Valve Body
A	B	F	E	L	A/F	Orifice (mm)	
83	96.5	14	32	65	27	12	PD5422BH15S04V

