

PNEUMATRON

www.pneumatron.co.za

sales01@pneumatron.co.za

5/2 Way Industrial valve Single Solenoid PDD520 Series directional solenoid valve

Specifications

Temperature: -5°C to 50°C
Pressure: 1.5 to 8 Bar
Joint Pipe Bore: Inlet/Outlet=1/4"
 Exshhaust=1/8"
Coil voltages: 24VDC (2.0W) & 220VAC (5.0VA)
 100% ED IP65
Max Action: 5 Cycles/Second
Response time: 0,5s
Body material: Aluminium Alloy
 (Dimensions page 2)



PDD520 Series 5/2 way Single Solenoid Valve

Inlet/Outlet port size	Exshhaust port size	Kv	Min pressure	Max pressure		Valve no
				AC (5VA)	DC (2W)	
1/4"	1/8"	0.89	1,5 Bar	8 Bar	8 Bar	PDD520-02S-XX

5/2 Way Industrial valve Double Solenoid PDD520 Series directional solenoid valve

Specifications

Temperature: -5°C to 50°C
Pressure: 1.5 to 8 Bar
Joint Pipe Bore: Inlet/Outlet=1/4"
 Exshhaust=1/8"
Coil voltages: 24VDC (2.0W)
 220VAC (5.0VA)
 100% ED IP65
Max Action: 5 Cycles/Second
Response time: 0,5s
Body material: Aluminium Alloy
 (Dimensions page 3)



PDD520 Series 5/2 way Double Solenoid Valve

Inlet/Outlet port size	Exshhaust port size	Kv	Min pressure	Max pressure		Valve no
				AC (5VA)	DC (2W)	
1/4"	1/8"	0.89	1,5 Bar	8 Bar	8 Bar	PDD520-02D-XX

