


# PNEUMATRON

www.pneumatron.co.za


sales01@pneumatron.co.za

## 2/2 Industrial Solenoid Valve PLZ22 Stainless Steel Series, High Pressure (N.C)

**Characteristic:** 1. High pressure solenoid valve with low power consumption  
2. Compact design to save the space



**Medium:** Air Gas, Water & Light oil ≤ 20 CST  
**Temperature:** VITON: -10°C to 140°C  
**Media Temperature:** Maximum 110°C  
**Pressure:** Water & air (1.5mm): 0 to 130 Bar (AC) 86 Bar (DC)  
 Water & air (3mm): 0 to 30 Bar (AC) 20 Bar (DC)  
 Light oil ≤ 20CST (1.5mm): 0 to 120 Bar (AC) 80 Bar (DC)  
 Light oil ≤ 20CST (3mm): 0 to 20 Bar (AC) 13 Bar (DC)  
**Body:** SS316  
**Port Size (BSP):** 1/4"  
**Orifice:** 1.5mm  
**Coil voltages:** 220VAC, 110VAC, 48VAC, 24VDC, 12VDC  
**Coils:** IP65, 100%ED



### PLZ22 Series, Normally Closed with Coil

Port Size	Orifice (mm)	KV	Min Pressure	Max Pressure		Seals Material	Body Material	Valve Body	Coil
				AC(19VA)	DC(17W)				
1/4"	1.5	0.69	0 Bar	130 Bar	86 Bar	VITON	SS316	PLZ22SH15S02V	C17
1/4"	3	0.22	0 Bar	30 Bar	20 Bar		Brass	PLZ22BH30S02V	C19

### Coil Specifications

Voltage	Inrush (50HZ VA)	Holding (50HZ VA)	Watt (DC)
AC220V		20	
AC110V		20	
AC48V			
DC24V			17
DC12V			17

# PNEUMATRON

[www.pneumatron.co.za](http://www.pneumatron.co.za)

[sales01@pneumatron.co.za](mailto:sales01@pneumatron.co.za)

## 2/2 Industrial Solenoid Valve

### PLZ22 Stainless Steel Series, High Pressure (N.C)

