


PNEUMATRON

www.pneumatron.co.za


sales01@pneumatron.co.za

2/2 Industrial Solenoid Valve PLZ22 Stainless Steel Series, High Pressure (N.C)

Characteristic: 1. High pressure solenoid valve with low power consumption
2. Compact design to save the space



Medium: Air Gas, Water & Light oil ≤ 20 CST
Temperature: VITON: -10°C to 140°C
Media Temperature: Maximum 110°C
Pressure: Water & air (1.5mm): 0 to 130 Bar (AC) 86 Bar (DC)
 Water & air (3mm): 0 to 30 Bar (AC) 20 Bar (DC)
 Light oil ≤ 20CST (1.5mm): 0 to 120 Bar (AC) 80 Bar (DC)
 Light oil ≤ 20CST (3mm): 0 to 20 Bar (AC) 13 Bar (DC)
Body: SS316
Port Size (BSP): 1/4"
Orifice: 1.5mm
Coil voltages: 220VAC, 110VAC, 48VAC, 24VDC, 12VDC
Coils: IP65, 100%ED



PLZ22 Series, Normally Closed with Coil

Port Size	Orifice (mm)	KV	Min Pressure	Max Pressure		Seals Material	Body Material	Valve Body	Coil
				AC(19VA)	DC(17W)				
1/4"	1.5	0.07	0 Bar	130 Bar	86 Bar	VITON	SS316	PLZ22SH15S02V	C17
1/4"	3	0.22	0 Bar	30 Bar	20 Bar		Brass	PLZ22BH30S02V	C19

Coil Specifications

Voltage	Inrush (50HZ VA)	Holding (50HZ VA)	Watt (DC)
AC220V		20	
AC110V		20	
AC48V			
DC24V			17
DC12V			17

PNEUMATRON

www.pneumatron.co.za

sales01@pneumatron.co.za

2/2 Industrial Solenoid Valve PLZ22 Stainless Steel Series, High Pressure (N.C)

